EASYDEK GLASS COVER 50 MU

DESCRIPTION:

Glass Cover is a transparent UV-resistant film for temporary protection of smooth surfaces such as glass, doors and window frames against damage of all kinds. The UV3-film is UV-resistant; the selfadhesive layer will not harden or leave adhesive residue on the glass.

Glass Cover offers maximum protection during new construction, renovation and maintenance work such as building maintenance, plastering, sanding, bricklaying, demolition or painting. Only use Glass Cover on dry, clean and fully-cured surfaces. Ensure the upper side is applied tightly just below the frame. This promotes adhesion considerably. Then smooth out the film to avoid air bubbles. Glass Cover can be removed easily after use and can be discarded as a small package.



APPLICATIONS:

- → PROTECT WINDOWS
- → PROTECT GLASS
- → PROTECT WINDOW FRAMES
- → COVER OTHER SURFACES

CHARACTERISTICS:

- → NO ADHESIVE RESIDUE
- → QUICK TO USE
- → GOOD ADHESION IN RAIN AND WIND
- → TRANSPARENT, ALLOWS LIGHT IN
- → CAN BE USED OVER AN EXTENDED PERIOD OF TIME

TECHNICAL DATA:

Application duration	180 days (max 40° C)
Storage	9 months (5° – 30° C) (dry, no direct sunlight)
Thickness	50 mu +/- 10%
Adhesion to steel	0.3 N/cm
Winding	Reversed wound
Core	Cardboard Tube

COMPOSITION:

Material	LLDPE UV3
Adhesion layer	Acrylic waterbased
Color	Blue / Transparent